

# THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 10/15/2015

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.  
Product code : TM5646

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine Flush

#### 1.3. Details of the supplier of the safety data sheet

Rev Your Cause LLC  
1440 Jason Way  
Unit 100-107  
Santa Maria, CA 93455  
T 805-925-2796

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Inhalation) H332  
Eye Irrit. 2B H320

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H302+H332 - Harmful if swallowed or if inhaled  
H320 - Causes eye irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing dust, fume, gas, mist, vapor, spray  
P264 - Wash affected areas thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P301+P312 - If swallowed: Call a poison center, doctor if you feel unwell  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.  
P330 - Rinse mouth  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	(CAS No) 64742-52-5	>= 95	Not classified

# THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
2-Butoxyethanol	(CAS No) 111-76-2	5 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: If you feel unwell, seek medical advice.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: Causes eye irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Evacuate area. No flames, no sparks. Eliminate all sources of ignition. No open flames. No smoking. Use special care to avoid static electric charges.
------------------	---

##### 6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Remove contaminated clothes.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.

#### 7.3. Specific end use(s)

Follow Label Directions.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	97 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> MIST 8 HOURS
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> MIST 8 HOURS

#### 8.2. Exposure controls

- Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear appropriate mask.
- Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Colourless to yellow.
- Odor : Petroleum-like odour. Sweet.
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : > 100 °C
- Flash point : > 121 °C

# THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature	: 315.6 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.868
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 23 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

VOC content	: 5 %
-------------	-------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: Harmful if inhaled.

2-Butoxyethanol (111-76-2)	
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg (435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value,435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-Butoxyethanol (111-76-2)	
IARC group	3

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
IARC group	3

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

# THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: Causes eye irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.	
Persistence and degradability	Not established.
2-Butoxyethanol (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.20 g O <sub>2</sub> /g substance
ThOD	2.305 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.31

### 12.3. Bioaccumulative potential

THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.	
Bioaccumulative potential	Not established.
2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

2-Butoxyethanol (111-76-2)	
Surface tension	0.027 N/m (25 °C)

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Avoid release to the environment.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground):	Not regulated,
ICAO/IATA (air):	Not regulated,
IMO/IMDG (water):	Not regulated,

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

### 14.3. Additional information

Other information : No supplementary information available.

### Overland transport

No additional information available

# THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
-------------------------------------	---------------------------------

#### 2-Butoxyethanol (111-76-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
-------------------------------------	---

#### Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard
-------------------------------------	---------------------------------

### 15.2. International regulations

#### CANADA

#### 2-Butoxyethanol (111-76-2)

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

#### 2-Butoxyethanol (111-76-2)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

#### 2-Butoxyethanol (111-76-2)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

### 15.3. US State regulations

#### THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

U.S. - California - Proposition 65 - Carcinogens List	No
---	----

U.S. - California - Proposition 65 - Developmental Toxicity	No
---	----

U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
---	----

U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
---	----

U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
---	----

#### 2-Butoxyethanol (111-76-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

# THROTTLE MUSCLE ENGINE FLUSH 16 FL.OZ.

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2-Butoxyethanol (111-76-2)

#### State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16: Other information

Other information : None.


Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*

# THROTTLE MUSCLE ENGINE FLUSH 1 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 10/15/2015

Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : THROTTLE MUSCLE ENGINE FLUSH 1 GALLON  
Product code : TM7326

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine Flush

#### 1.3. Details of the supplier of the safety data sheet

Rev Your Cause LLC  
144O Jason Way  
Unit 100-107  
Santa Maria, CA 93455  
T 805-925-2796

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Inhalation) H332  
Eye Irrit. 2B H320

Full text of H statements : see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H302+H332 - Harmful if swallowed or if inhaled  
H320 - Causes eye irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing dust, fume, gas, mist, vapor, spray  
P264 - Wash affected areas thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P301+P312 - If swallowed: Call a poison center, doctor if you feel unwell  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.  
P330 - Rinse mouth  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

#### 2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Heavy Naphthenic	(CAS No) 64742-52-5	>= 95	Not classified



# THROTTLE MUSCLE ENGINE FLUSH 1 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
2-Butoxyethanol	(CAS No) 111-76-2	5 - 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

The exact percentage is a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : If you feel unwell, seek medical advice.
- Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- Symptoms/injuries after skin contact : May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
- Symptoms/injuries after eye contact : Causes eye irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
- Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Evacuate area. No flames, no sparks. Eliminate all sources of ignition. No open flames. No smoking. Use special care to avoid static electric charges.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Safety glasses.
- Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Dam up the liquid spill. Contain released substance, pump into suitable containers. Plug the leak, cut off the supply.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

# THROTTLE MUSCLE ENGINE FLUSH 1 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Remove contaminated clothes.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.

#### 7.3. Specific end use(s)

Follow Label Directions.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	97 mg/m <sup>3</sup>
USA ACGIH	ACGIH TWA (ppm)	20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> MIST 8 HOURS
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> MIST 8 HOURS

#### 8.2. Exposure controls

- Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear appropriate mask.
- Other information : Do not eat, drink or smoke during use.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Color : Colourless to yellow.
- Odor : Petroleum-like odour. Sweet.
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : > 100 °C
- Flash point : > 121 °C

# THROTTLE MUSCLE ENGINE FLUSH 1 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature	: 315.6 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.868
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 23 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

VOC content	: 5 %
-------------	-------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: Harmful if inhaled.

2-Butoxyethanol (111-76-2)	
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg (435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value,435 mg/kg bodyweight; Rabbit; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg body weight
LC50 inhalation rat (mg/l)	> 5.2 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

2-Butoxyethanol (111-76-2)	
IARC group	3

Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
IARC group	3

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

# THROTTLE MUSCLE ENGINE FLUSH 1 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met. Harmful if swallowed.
Symptoms/injuries after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: May cause slight irritation . Itching. Red skin. Skin rash/inflammation.
Symptoms/injuries after eye contact	: Causes eye irritation. Irritation of the eye tissue. Inflammation/damage of the eye tissue. Redness of the eye tissue.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

THROTTLE MUSCLE ENGINE FLUSH 1 GALLON	
Persistence and degradability	Not established.
2-Butoxyethanol (111-76-2)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	0.71 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	2.20 g O <sub>2</sub> /g substance
ThOD	2.305 g O <sub>2</sub> /g substance
BOD (% of ThOD)	0.31

#### 12.3. Bioaccumulative potential

THROTTLE MUSCLE ENGINE FLUSH 1 GALLON	
Bioaccumulative potential	Not established.
2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (Experimental value; BASF test; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

#### 12.4. Mobility in soil

2-Butoxyethanol (111-76-2)	
Surface tension	0.027 N/m (25 °C)

#### 12.5. Other adverse effects

Other information : Avoid release to the environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations. . Avoid release to the environment.
Ecology - waste materials	: Avoid release to the environment.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground):	Not regulated,
ICAO/IATA (air):	Not regulated,
IMO/IMDG (water):	Not regulated,

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not regulated

#### 14.3. Additional information

Other information : No supplementary information available.

#### Overland transport

No additional information available

# THROTTLE MUSCLE ENGINE FLUSH 1 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

THROTTLE MUSCLE ENGINE FLUSH 1 GALLON	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
2-Butoxyethanol (111-76-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard

### 15.2. International regulations

#### CANADA

2-Butoxyethanol (111-76-2)
Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

2-Butoxyethanol (111-76-2)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Carc.Cat.2; R45

Full text of R-phrases: see section 16

#### 15.2.2. National regulations

2-Butoxyethanol (111-76-2)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Korean ECL (Existing Chemicals List) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

### 15.3. US State regulations

THROTTLE MUSCLE ENGINE FLUSH 1 GALLON				
U.S. - California - Proposition 65 - Carcinogens List	No			
U.S. - California - Proposition 65 - Developmental Toxicity	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No			
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No			
2-Butoxyethanol (111-76-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Distillates (Petroleum), Hydrotreated Heavy Naphthenic (64742-52-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

# THROTTLE MUSCLE ENGINE FLUSH 1 GALLON

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2-Butoxyethanol (111-76-2)

#### State or local regulations

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
U.S. - New Jersey - Right to Know Hazardous Substance List

### SECTION 16: Other information

Other information : None.


Full text of H-phrases:

H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



#### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Personal Protection : B

SDS US (GHS HazCom 2012) - TCC

*The Supplier identified in Section 1 of this MSDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product*

*Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.*